



REV	DESCRIPTION	DATE	CHECK
A1	Add "G" to the original Article No. .	2025-10-16	FDL
A2	Modify the Torque tolerance:25±8 to 25±10; 60±10 to 60±15;120±15 to 120±20; 150±15 to 150±25;180±20 to 180±25.	2026-4-7	FDL



- Notes:
- Material:
(Body and Cap) PC UL94 V2,
(Gear and Shaft) POM UL94 HB;
 - Color: Black;
 - RoHS Compliant.

Type	Standard Spur
Teeth Profile	Involute Full Depth
Pressure Angle	20°
Number of Teeth	11
Module	0.8
Durability	30000 cycles

Part No.	Article No.	Torque (gf.cm) @20 RPM&23℃	Identification Paint Mark
30170	GDMP-E-25	25±10	White
30171	GDMP-E-40	40±10	Yellow
30172	GDMP-E-60	60±15	Purple
30173	GDMP-E-80	80±15	Green
30175	GDMP-E-120	120±20	Black
30176	GDMP-E-150	150±25	Red
30307	GDMP-E-180	180±25	Blue

Gecko International Co.						DATE	2026-4-7	DIMENSION	TOLERANCE
TITLE	ROTARY DAMPER WITH GEAR					SCALE	FIT	L≤4	±0.10
ARTICLE NO.	GDMP-E	MOLD NO.	/	DRAW	LWJ	UNIT	MM	4< L≤15	±0.20
PART NO.	SEE TABLE	MATERIAL	SEE NOTES	DESIGN	LWJ	VERSION	A2	15< L≤50	±0.30
DWG NO.	E3072	COLOR	SEE NOTES	APPROVAL	FDL	VIEW		50< L≤100	±0.40