




- Notes:
- 1. Color: Natural;
 - 2. RoHS Compliant;
 - 3. Hole: $\varnothing 6.0 \pm 0.08 \text{mm}$;
Panel Thickness: 0.8-2.0mm.

Part No.	Article No.	Part No.	Article No.	A	D Bundle Dia.
60815	GSOTL4-25-4M-66	60816	GSOTL4-25-4M-V0	4.0	5.1-7.6
60270	GSOTL4-25-1-66	60533	GSOTL4-25-1-V0	4.8	
60271	GSOTL4-25-2-66	60534	GSOTL4-25-2-V0	12.7	
60272	GSOTL4-25-3-66	60535	GSOTL4-25-3-V0	19.1	
60273	GSOTL4-25-4-66	60536	GSOTL4-25-4-V0	25.4	
60274	GSOTL4-25-5-66	60537	GSOTL4-25-5-V0	31.8	
Material: PA66 UL94V2		Material: PA66 UL94V0			

Gecko International Co.						DATE	2025-12-30	DIMENSION	TOLERANCE
TITLE	STAND-OFF TWIST LOCK					SCALE	FIT	$L \leq 4$	± 0.10
ARTICLE NO.	GSOTL4-25	MOLD NO.	S0393	DRAW	JF	UNIT	MM	$4 < L \leq 15$	± 0.20
PART NO.	SEE TABLE	MATERIAL	SEE TABLE	DESIGN	JF	VERSION	A0	$15 < L \leq 50$	± 0.30
DWG NO.	E6104	COLOR	SEE NOTES	APPROVAL	FDL	VIEW		$50 < L \leq 100$	± 0.40