


Notes:

- 1.Material: PA66 UL94V2;
- 2.Color: Natural;
- 3.RoHS Compliant;
- 4.Minimum Hole Dia. : Ø25.4 mm

| Part No. | Article No. | Panel Thickness(Ref.) | A<br>+0.38/-0.13 | B<br>+0.38/-0.13 | C<br>+0.38/-0.13 | D<br>+0.38/-0.13 |
|----------|-------------|-----------------------|------------------|------------------|------------------|------------------|
| 60976    | GMGS-1-01   | 0.4-1.3               | 3.8              | 1.4              | 1.4              | 2.5              |
| 60977    | GMGS-2-01   | 1.3-2.2               | 4.4              | 2.3              | 1.4              | 2.5              |
| 60978    | GMGS-4-01   | 3.3-4.9               | 8.3              | 5.0              | 1.8              | 4.1              |

| Gecko International Co. |                      |          |           |          |     | DATE    | 2025-7-1                                                                              | DIMENSION    | TOLERANCE |
|-------------------------|----------------------|----------|-----------|----------|-----|---------|---------------------------------------------------------------------------------------|--------------|-----------|
| TITLE                   | MOLDED GROMMET STRIP |          |           |          |     | SCALE   | FIT                                                                                   | L≤4          | ±0.10     |
| ARTICLE NO.             | GMGS                 | MOLD NO. | SEE TABLE | DRAW     | JF  | UNIT    | MM                                                                                    | 4 < L ≤ 15   | ±0.20     |
| PART NO.                | SEE TABLE            | MATERIAL | SEE NOTES | DESIGN   | JF  | VERSION | A0                                                                                    | 15 < L ≤ 50  | ±0.30     |
| DWG NO.                 | E6271                | COLOR    | SEE NOTES | APPROVAL | FDL | VIEW    |  | 50 < L ≤ 100 | ±0.40     |